

## RECOMMENDED TIRE PRESSURE

Rider Weight (kg)	Rim Model (s)	FIFTY (T.E.), THIRTY, FIFTY, EIGHTY				TWENTY, THIRTY, FIFTY, SIXTY				THREE, ZERO		
	Rim Profile type	Racing Road				All-Road				Specialty Wheels		
	Inner Width	17-18mm				21mm				15mm		
	Tire size (700c)	23mm	25mm	28mm	30mm	23mm	25mm	28mm	30mm	23mm	25mm	28mm
40		4.1	3.7	3.1	2.5	3.8	3.3	2.8	2.1	4.8	4.3	3.8
45		4.5	3.9	3.4	2.8	4.1	3.6	3.0	2.4	5.2	4.6	4.1
50		4.8	4.2	3.6	2.9	4.5	3.9	3.2	2.6	5.5	4.9	4.3
55		5.2	4.5	3.9	3.2	4.8	4.1	3.5	2.8	5.9	5.2	4.6
60		5.5	4.8	4.1	3.3	5.2	4.4	3.7	3.0	6.2	5.4	4.8
65		5.9	5.1	4.3	3.5	5.5	4.8	4.0	3.2	6.6	5.8	5.0
70		6.2	5.4	4.6	3.7	5.9	5.0	4.2	3.3	6.9	6.1	5.2
75		6.6	5.7	4.8	3.9	6.1	5.2	4.4	3.5	7.0	6.1	5.3
80		6.9	6.0	5.1	4.1	6.4	5.5	4.6	3.7	7.2	6.3	5.4
85		7.2	6.2	5.3	4.3	6.7	5.7	4.8	3.9	7.4	6.6	5.7
90		7.4	6.4	5.5	4.6	7.0	5.9	5.0	4.1	7.6	6.6	5.7
95		7.7	6.6	5.7	4.6	7.4	6.3	5.3	4.2	7.9	6.9	5.9
100		7.9	6.8	5.8	4.7	7.5	6.4	5.4	4.3	8.1	7.0	6.1

Note 1: Tire pressures shown are in **BAR**.

Note 2: Above tire pressure values are only recommendations that should be adjusted accordingly based on rider weight, preference and intended usage with a tubeless clincher tire.

Note 3: For optimal performance, it might be necessary to adjust the tire pressure by incremental pressures of +/- 5 psi.

Note 4: The recommended tire pressures above are for paved road usage only. For light off-road use such as gravel, please adjust tire pressure accordingly based on riding style and intended usage.

Note 5: For tubeless setups always follow the original tire manufacturer's installation instructions to ensure a tight and secure fit between tire and rim. Always use original tubeless parts during installation.

